









PRODUCT DESCRIPTION

- » Shank Ø6 mm
- » Pink aluminium oxide
- » Ceramic bond, medium
- » High material removal rate
- » For cast steel and for alloyed and pre-toughened steel



	Shape	d3	d1	l1	Grit	 Pcs. / PU	No.	EUR	
A1		Cylinder	6	8	10	60	10	V 72442/ A1/ 8x10/ 60	<>
			6	10	13	60	10	V 72442/ A1/10x13/ 60	<>
			6	13	13	46	10	V 72442/ A1/13x13/ 46	<>
			6	16	20	46	10	V 72442/ A1/16x20/ 46	<>
			6	20	20	36	10	V 72442/ A1/20x20/ 36	<>
C1		Wheel	6	13	3	80	10	V 72442/ C1/13x 3/ 80	<>
			6	16	4	60	10	V 72442/ C1/16x 4/ 60	<>
			6	20	6	60	10	V 72442/ C1/20x 6/ 60	<>
			6	25	6	60	10	V 72442/ C1/25x 6/ 60	<>
E1		Inverted cone	6	20	20	60	10	V 72442/ E1/20x20/ 60	<>
G1		Cone	6	16	32	46	10	V 72442/ G1/16x32/ 46	<>
			6	20	32	36	10	V 72442/ G1/20x32/ 36	<>
J1		Ball	6	8	-	60	10	V 72442/ J1/ 8/ 60	<>
			6	10	-	60	10	V 72442/ J1/10/ 60	<>
			6	13	-	46	10	V 72442/ J1/13/ 46	<>
L1		Tree, pointed tip	6	5	10	80	10	V 72442/ L1/ 5x10/ 80	<>
			6	8	16	60	10	V 72442/ L1/ 8x16/ 60	<>
			6	10	20	60	10	V 72442/ L1/10x20/ 60	<>
			6	13	20	46	10	V 72442/ L1/13x20/ 46	<>

REFERENCE VALUES FOR V 72422, V 72423, V 72442

