



### PRODUCT DESCRIPTION

- » Made of special, heat-resistant tool steel
- » Optimal running smoothness due to hard turned shanks
- » Slim design
- » With Balluff chip hole

### APPLICATION

- » For clamping tools with cylindrical shank made of carbide or HSS and with h6 shank tolerance
- » Suitable for inductive, contact and hot air shrinking devices

d	d2	Interface	d1	A	No.	EUR
18	9	SK 40	3	120	HWZ 2269/SK40/ 3/120	<>
15	10	SK 40	4	80	HWZ 2269/SK40/ 4/ 80	<>
19	10	SK 40	4	120	HWZ 2269/SK40/ 4/120	<>
20	11	SK 40	5	120	HWZ 2269/SK40/ 5/120	<>
19	12	SK 40	6	80	HWZ 2269/SK40/ 6/ 80	<>
23	12	SK 40	6	120	HWZ 2269/SK40/ 6/120	<>
21	14	SK 40	8	80	HWZ 2269/SK40/ 8/ 80	<>
25	14	SK 40	8	120	HWZ 2269/SK40/ 8/120	<>
27	16	SK 40	10	120	HWZ 2269/SK40/10/120	<>
29	18	SK 40	12	120	HWZ 2269/SK40/12/120	<>