


### PRODUCT DESCRIPTION

- » For the marking of materials up to a strength of 1200 N/mm<sup>2</sup>
- » Characters according to DIN 1451
- » Hardness of the engraving 58 - 61 HRC



b	l	s	h <sup>1)</sup>	Type <sup>2)</sup>	 Pcs. / PU	No.	EUR
7	75	7	2	0-9	9	V 28800/ 2/0-9	<>
8	75	8	3	0-9	9	V 28800/ 3/0-9	<>
9	80	9	4	0-9	9	V 28800/ 4/0-9	<>
10	80	10	5	0-9	9	V 28800/ 5/0-9	<>
12	85	12	6	0-9	9	V 28800/ 6/0-9	<>
14	90	14	8	0-9	9	V 28800/ 8/0-9	<>
16	90	16	10	0-9	9	V 28800/10/0-9	<>
7	75	7	2	A-Z	27	V 28800/ 2/A-Z	<>
8	75	8	3	A-Z	27	V 28800/ 3/A-Z	<>
9	80	9	4	A-Z	27	V 28800/ 4/A-Z	<>
10	80	10	5	A-Z	27	V 28800/ 5/A-Z	<>
12	85	12	6	A-Z	27	V 28800/ 6/A-Z	<>
14	90	14	8	A-Z	27	V 28800/ 8/A-Z	<>
16	90	16	10	A-Z	27	V 28800/10/A-Z	<>

1) h: font size

2) 0-9: 9 stamped numbers 0-9  
A-Z: 27 stamped letters A-Z incl. &